

Louvered—Premium Wood

Shutter Specifications



Shown with Divider Rail

Materials Available:	Solid Kiln Dried Red Grandis Solid Kiln Dried Cedar Solid Kiln Dried Mahogany	
Finishes Available: Unfinished—ready to prime and paint or stain Factory Primed—ready to lightly sand and paint Factory Painted—9 standard, unlimited custom colors		
Assembly: 2 dowels with polyurethane exterior glue and 3.5" threaded screw at each joint		
Hardware: Fixed mounting hardwo	are available	

Links to endorsed provider for functional hardware

Pricing & Ordering:

Online at shutterland.com





Measure Shutters

Install Shutters

SHUTTER SIZES	Widths: 10" - 32" (.25" increments) Heights: 15" - 108" (.25" increments)		
LOUVER SIZES	1.75" louvers	1.5" louvers (+\$)	
	.25" thick	.25" thick	
	15° angle spaced on 1.75" centers	15° angle spaced on 1.5" centers	
TOP RAIL	3.5" height	3" height	
	Arch Top Available	Arch Top Available	
DIVIDER RAIL(s)	3.5" height	3" height	
one or two	Required on shutters over 90"	Required on shutters over 90"	
	Location measured from bottom of shutter to center of divider	Location measured from bottom of shutter to center of divider	
BOTTOM RAIL dependent on shutter height	3.5 - 5" height	3"- 4.25" height	
SIDE STILES	2.125" wide		
THICKNESS	1.5" thick		
BACK STRAP	Added to panels 19" or wider to maintain louver alignment		